

Dimensions	Thickness	Width	Length
Drain gutter from BELMONDO® Walkpro	16 mm	16.7 cm	100 cm
Drain gutter from BELMONDO® Paddock	24 mm	16.7 cm	100 cm

Installation

BELMONDO® horse mats can be simply installed on any paved ground. Normally, fixing the mats to the floor is not necessary (floating installation method). Due to their weight and the precise puzzle interlock system, the mats remain stable on the floor. Edge offcuts can often be used in other places, thereby minimizing waste!

[Installation instructions](#)

Suitable for every type of shoe.

Compatibility with vehicle traffic

BELMONDO® Gully is compatible with vehicle traffic, e.g. farm yard loader or tractor with authorized pneumatic tires for recommended inflation pressure up to max. 2.5 bar. (Note: Drive with the necessary caution and ensure adequately large turning radii!)

[Vehicle traffic specifications](#)

Maintenance tip

Treatment with a high-pressure cleaner and standard cleaning agents possible. The interlocked single mats can simply be folded up or removed for basic cleaning and subsequently re-installed.

Tolerances

Thickness: +3/-2 mm

Width + length: +/- 1,5 % (DIN ISO 3302-1 tolerance class M4)

Please refer to the relevant KRAIBURG specifications and installation instructions, which provide valuable hints and tips.

More technical details on request. The products featured here are exclusively intended for the demonstrated applications. Technical details subject to change. Our General Terms and Conditions apply. Legal basis is the German version of the document.