BELMONDO® Gully
Safety & reliable drainage

Stable walkway **Washdown area** **Indoor washdown area**

Safety and reliable drainage

Particularly practical at the washdown area:
BELMONDO® Gully is the smart solution for the area around the drain: With the custom-fit **cut from BELMONDO® Walkpro or BELMONDO® Paddock** stable mat, gullies are safely covered without sealing them. Measuring 40 × 40 cm, it is ideal for large drains. For smaller gullies, BELMONDO® Gully can simply be cut to size (14 × 14 cm). This allows water to drain quickly, avoids tripping edges, and metal edges are safely covered.



- **Safe covering of metal elements**
- **Tripping hazards are avoided**
- **Drain remains functional**
- **Can be cut to size flexibly (outer dimensions 40 x 40 cm or 14 x 14 cm)**

BELMONDO® Gully: Technical data

Gummiwerk KRAIBURG Elastik GmbH & Co. KG

Göllstraße 8 | 84529 Tittmoning, Germany | Phone: +49 8683 701-303 | E-mail: belmondo@kraiburg-elastik.de
kraiburg-belmondo.com

Dimensions	Thickness	Width	Length
Gully from BELMONDO® Walkpro	16 mm	40 cm	40 cm
Gully from BELMONDO® Paddock	24 mm	40 cm	40 cm

Installation

BELMONDO® horse mats can be simply installed on any paved ground. Normally, fixing the mats to the floor is not necessary (floating installation method). Due to their weight and the precise puzzle interlock system, the mats remain stable on the floor. Edge offcuts can often be used in other places, thereby minimizing waste!
Installation instructions

Suitable for every type of shoe.

Compatibility with vehicle traffic

BELMONDO® Gully is compatible with vehicle traffic, e.g. farm yard loader or tractor with authorized pneumatic tires for recommended inflation pressure up to max. 2.5 bar. (Note: Drive with the necessary caution and ensure adequately large turning radii!)
Vehicle traffic specifications

Maintenance tip

Treatment with a high-pressure cleaner and standard cleaning agents possible. The interlocked single mats can simply be folded up or removed for basic cleaning and subsequently re-installed.

Tolerances

Thickness: +3/-2 mm
Width + length: +/– 1,5 % (DIN ISO 3302–1 tolerance class M4)

Please refer to the relevant KRAIBURG specifications and installation instructions, which provide valuable hints and tips.

More technical details on request. The products featured here are exclusively intended for the demonstrated applications. Technical details subject to change. Our General Terms and Conditions apply. Legal basis is the German version of the document.

Care and usage instructions:
Our flooring for horse husbandry is tested for its slip resistance under defined test conditions. However, the actual slip resistance in practical use depends on the relevant environmental and usage conditions. Especially moisture, dirt, mud, ice or snow, the slope, the condition of the ground and wear or damage can adversely affect performance characteristics. Individual factors such as hoof condition, shoe, health status and the animals' movement behavior also affect slip resistance. Surfaces must therefore be checked regularly according to the relevant usage conditions, maintained and kept in proper condition.

Gummiwerk KRAIBURG Elastik GmbH & Co. KG

Göllstraße 8 | 84529 Tittmoning, Germany | Phone: +49 8683 701-303 | E-mail: belmondo@kraiburg-elastik.de
kraiburg-belmondo.com